

# University School of Chemical Technology GURU GOBIND SINGH INDRAPRASTHA UNIVERSITY

Sector: 16C, Dwarka, New Delhi-110 078

Ref. No.: GGSIPU/USCT/PROJECT/PUR/2024/2

Date: 26.02.2024

## NOTICE INVITING QUOTATION

Sealed item rate quotations are invited on behalf of Dean, University School of Chemical Technology, Guru Gobind Singh Indraprastha University, Sector: 16C, Dwarka, New Delhi-110078. from manufacturers/distributors/authorized dealers for the supply of following item with the following technical specifications, eligibility and terms and conditions:

S. No.	Item	Technical Specifications	Qty.
1.	Electro- ultrafiltration membrane set-up	An electro-ultrafiltration membrane set-up constructed with Teflon/Perspex, should be provided with feed inlet, retentate outlet, permeate outlet and appropriate perforated stainless steel (SS) membrane support. Module should be mounted on a painted iron structure (3.4 ft. high). Permeation should be from the bottom of the channel through a common outlet. Feed inlet should be provided with a distributor. To avoid channeling, bottom surface of the flow channel should be grooved and connected to a common outlet for permeate collection. Module should have pressure gauge for measuring pressure inside the chamber.  Channel height should be maintained using appropriate gasket. Maximum liquid holdup should be 400 mL in the pipe line. SS 316 plate (length: 15 cm, width: 5 cm; thickness: 1.0 cm) would require to be fixed with the upper part of the membrane module flow channel so that external de power can be supplied through the SS-316 plate and also through the SS-316 porous membrane support (length: 20 cm, width: 10 cm; thickness: 1.0 mm) placed at the bottom of the channel. Set up should be provided with the following technical details.  Technical Details:  (i) Membrane Module: (i) Material: Teflon/Perspex; (ii) Flow channel: Length: 20 cm, Width: 10 cm; (iii) Channel height: 15-18 mm; (iv) Operating pressure: 15 to 150 psi; (v) Pressure gauge: Up to at least 200 psi (No.: 03); (vi) Rotameter: 5-300 LPH (No.: 03); (vii) Number of gaskets: Three; (viii) Nuts and bolts with spanners: Stainless steel (two sets).  (ii) Cylindrical Feed Tank: Capacity: 2.0 Liter (Max.), Tank diameter: 12 cm (Max.); Material - SS 304; Wall thickness: 2 mm (min.), Top Cover - Flange types. Feed tank should have provision for bypass and retentate circulation. Also, it should have proper drainage system. All the connected pipes/tubes should be capable of handling high pressure liquid.  (iii) Feed Pump: Max Speed - 1600 RPM; Pressure - 15-150 psi; Flow: 5-300 LPH; Types: Plunger (SS); Motor: PMDC. Control - Manual with Dial. Pump configuration	

- Supplier must have valid registration of GST.
- Should have valid PAN number.

## Terms & Conditions:

Delivery: F.O.R. GGSIP University, Sector 16 C, Dwarka, New Delhi-110078

Delivery period: Max. 30 days.

Supply after the stipulated delivery period will not be accepted.

GST: GST as applicable may please be clearly mentioned in the quotation.

Payment: After satisfactory Installation and demonstration. No advance payment will be made.

Quotations received after due date & time shall be summarily rejected.

12.03.2024, 5:00 PM, Room No. 105, Block B, USCT, GGSIPU, Sector 16 C, Last date, time and venue for submission of Dwarka, New Delhi - 110078 quotation

### Copy to:

- 1. In-Charge, Server Room-with a request to upload the same on University Website
- 2. Project file

